

Boat Details

| | | | |
|------------|----------|--------------|----------------------------|
| Price | POA | Boat Brand | Mercury |
| Model | 250 HP | Length | 0.00 |
| Year | 2022 | Category | Boat Engines and Outboards |
| Hull Style | | Hull Type | |
| Power Type | | Stock Number | 0 |
| Condition | New | State | New Zealand |
| Suburb | Pukekohe | Engine Make | |

Description

The new Mercury 250hp FourStroke is precision engineered from skeg to cowl. Packed with advanced technology to improve all aspects of performance and reliability. The Robust 4.6 Litre V-8 engine is designed to minimise weight and maximise fuel economy. Delivering Mercury's best ever FourStroke hole shot, top speed and fuel efficiency. The 250hp FourStroke now comes with a 3+3=6 Year factory warranty. ENGINE DETAILS

Quick-revving double-overhead camshaft design and deep-breathing intake deliver thrilling and satisfying performance. Great for aluminum console, deck, inflatable rigid hull, inshore fishing, offshore fishing, and runabout boats and tritoons. SPECIFICATIONS - 250

HP / kW

- 250 / 186

Engine type

- V-8

MidSection

- Conventional MidSection

Displacement (CID/CC)

- 279 CID

Displacement (L)

- 4.6L

Cylinder Configuration

- V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves

Full throttle RPM

- 5200-6000

Air induction

- Performance-Tuned Long-Runner Intake Manifold

Fuel induction system

- Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization

Alternator amp / Watt

- 85-amp (1071 Watt) with Idle Charge

Recommended fuel

- Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

- NMMA Certified FCW SAE 10W-30

Engine protection operator warning system

- SmartCraft Engine Guardian

Compatible with SmartCraft digital technology

- Yes

Starting

- Electric Start with SmartStart Protection

Controls

- Remote Mechanical or Digital Throttle & Shift (DTS)

Steering

- Big Tiller (optional)
- Hydraulic (standard)
- Power (optional)

Shaft length

- 20" / 508 mm

- 25" / 635 mm
- 30" / 762 mm

Gearcase ratio

- 1.75:1

Dry weight *Lightest model available

- 527 lbs / 239 kgs

CARB star rating

- 3

Bore and stroke

- 3.6 in x 3.4 in / 92 mm x 86 mm

Ignition

- SmartCraft PCM 112 Digital Inductive

Cooling system

- Water-cooled with thermostat

Gear shift

- F-N-R

Gearcase options

- 5.44"

Trim system

- Power trim and tilt

Exhaust system

- Through prop

Counter Rotation

- Available

Color

- Cold Fusion White
- Pearl Fusion White
- Phantom Black
- Warm Fusion White

Lubrication system

- Integrated wet sump

Oil Capacity

- 7.0 Quarts / 6.6 Liters

Maximum Trim Range

- 20° (-6° to 14°)

Maximum Tilt Range

- 73° (-6° to 67°)

Engine Details

Displacement

4.6

Horse Power

250

Steering

Big Tiller (optional), Hydraulic (standard), Power (optional)

Fuel Capacity

6.6