

Boat Details

Price	POA	Boat Brand	Mercury
Model	150 HP Sea Pro Fourstroke	Length	0.00
Year	2021	Category	Boat Engines and Outboards
Hull Style		Hull Type	
Power Type		Stock Number	0
Condition	New	State	New Zealand
Suburb	Pukekohe	Engine Make	Mercury

Description

Mercury Seapro 150 HP Fourstroke - These commercial outboards are designed to work as hard as you do...engineered to be ultra tough working partners for anyone making their living on the water. Every SeaPro features unique components to cope with the additional demands of professional operation. Whatever your job there's a specific FourStroke of TwoStroke Mercury SeaPro model that's up to the task.

HP / kW

- 150 / 110

Engine type

- 8-valve single overhead cam (SOHC)
- Inline 4

Displacement (L)

- 3.0

Full throttle RPM

- 4800-5300

Air induction

- Performance-Tuned Scroll Intake Manifold

Fuel induction system

- Computer Controlled Multi-Port Electronic Fuel Injection (EFI)

Alternator amp / Watt

- 60 amp / 756 watt (Belt-Driven)

Recommended fuel

- Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

- NMMA Certified FCW 25W-40 Synthetic Blend

Engine protection operator warning system

- SmartCraft Engine Guardian

Compatible with SmartCraft digital technology

- Yes

Starting

- Electric (turn-key)
- Smart Start Electric

Controls

- Mechanical throttle & shift

Steering

- Big Tiller Compatible
- Dual Cable Mechanical
- Electro-Hydraulic Power Steering Optional on Duals
- Hydraulic power steering

Shaft length

- 20" / 508 mm
- 25" / 635 mm

Gearcase ratio

- 1.92:1

Dry weight \*Lightest model available

- 455 lbs / 206 kg

Emissions Star Rating

- 3

Bore and stroke

- 4.0 x 3.6" / 102 x 92 mm

Ignition

- SmartCraft ECM 70 Digital Inductive

Fuel system

- Electronic Fuel Injection (EFI)

Cooling system

- Water-cooled with thermostat

Gear shift

- F-N-R

Trim system

- Power Tilt
- Power Trim

Exhaust system

- Through prop

Counter rotation

- Available

Color

- Phantom Black

Lubrication system

- Integrated Dry Sump

Oil Capacity

- 6.3 qts / 6.0l

Maximum Trim Range

- 22° (-6° to 16°)

Maximum Tilt Range

- 73° (-6° to 67°)

Features

Horse Power (hp)150

Engine Details

Engine MakeMercury

Horse Power150